



Permit Weight Table 4

REVISED 01-2023

WHEEL BASE	2 Axles	3 Axles	4 Axles	5 Axles	6 Axles	7 Axles	8 Axles	9 Axles	10 Axles	11 Axles	12 Axles	13 Axles	14 Axles	15 Axles or more
4	43,000													
5	43,000													
6	43,000													
7	43,000													
8	43,000													
OVER 8' (BUT LESS THAN 8'6")														
	43,000	57,600												
9	43,000	58,800												
10	43,000	64,500	65,000											
11	43,000	64,500	68,200											
12	43,000	64,500	70,400											
13	43,000	64,500	72,600											
14	43,000	64,500	74,800											
15	43,000	64,500	77,000											
16	43,000	64,500	79,200											
17	43,000	64,500	81,400											
18	43,000	64,500	83,600											
19	43,000	64,500	85,800											
20	43,000	64,500	86,000	88,000										
21	43,000	64,500	86,000	90,200										
22	43,000	64,500	86,000	92,400										
23	43,000	64,500	86,000	94,600										
24	43,000	64,500	86,000	96,800										
25	43,000	64,500	86,000	99,000										
26	43,000	64,500	86,000	101,200										
27	43,000	64,500	86,000	103,400										
28	43,000	64,500	86,000	105,600										
29	43,000	64,500	86,000	107,500	107,800									
30	43,000	64,500	86,000	107,500	110,000									
31	43,000	64,500	86,000	107,500	113,600									
32	43,000	64,500	86,000	107,500	115,200									
33	43,000	64,500	86,000	107,500	116,800									
34	43,000	64,500	86,000	107,500	118,400									
35	43,000	64,500	86,000	107,500	120,000									
36	43,000	64,500	86,000	107,500	121,600									
37	43,000	64,500	86,000	107,500	123,200									
38	43,000	64,500	86,000	107,500	124,800									
39	43,000	64,500	86,000	107,500	126,400									
40	43,000	64,500	86,000	107,500	128,000									
41	43,000	64,500	86,000	107,500	129,000	129,000								
42	43,000	64,500	86,000	107,500	129,000	131,200								
43	43,000	64,500	86,000	107,500	129,000	132,800								
44	43,000	64,500	86,000	107,500	129,000	134,400								
45	43,000	64,500	86,000	107,500	129,000	136,000								
46	43,000	64,500	86,000	107,500	129,000	137,600								
47	43,000	64,500	86,000	107,500	129,000	139,200								
48	43,000	64,500	86,000	107,500	129,000	140,800								
49	43,000	64,500	86,000	107,500	129,000	142,400								
50	43,000	64,500	86,000	107,500	129,000	144,000								
51	43,000	64,500	86,000	107,500	129,000	145,600								
52	43,000	64,500	86,000	107,500	129,000	147,200								
53	43,000	64,500	86,000	107,500	129,000	148,800								
54	43,000	64,500	86,000	107,500	129,000	150,400								
55	43,000	64,500	86,000	107,500	129,000	150,500	152,000							
56	43,000	64,500	86,000	107,500	129,000	150,500	153,600							
57	43,000	64,500	86,000	107,500	129,000	150,500	155,200							
58	43,000	64,500	86,000	107,500	129,000	150,500	156,800							
59	43,000	64,500	86,000	107,500	129,000	150,500	158,400							
60	43,000	64,500	86,000	107,500	129,000	150,500	160,000							
61	43,000	64,500	86,000	107,500	129,000	150,500	161,600							
62	43,000	64,500	86,000	107,500	129,000	150,500	163,200							
63	43,000	64,500	86,000	107,500	129,000	150,500	164,800							
64	43,000	64,500	86,000	107,500	129,000	150,500	166,400							
65	43,000	64,500	86,000	107,500	129,000	150,500	168,000							
66	43,000	64,500	86,000	107,500	129,000	150,500	169,600							
67	43,000	64,500	86,000	107,500	129,000	150,500	171,200							
68	43,000	64,500	86,000	107,500	129,000	150,500	172,000	172,800						
69	43,000	64,500	86,000	107,500	129,000	150,500	172,000	174,400						
70	43,000	64,500	86,000	107,500	129,000	150,500	172,000	176,000						
71	43,000	64,500	86,000	107,500	129,000	150,500	172,000	177,600						
72	43,000	64,500	86,000	107,500	129,000	150,500	172,000	179,200						
73	43,000	64,500	86,000	107,500	129,000	150,500	172,000	180,800						
74	43,000	64,500	86,000	107,500	129,000	150,500	172,000	182,400						
75	43,000	64,500	86,000	107,500	129,000	150,500	172,000	184,000						

The loaded weight of a group of axles, vehicles, or combination of vehicles shall not exceed that specified in this permit weight table or any of the following:

*The manufacturer's side wall tire rating but not to exceed 600 pounds per inch of tire width;
 21,500 pounds per single axle;
 43,000 pounds per tandem axle;
 The weight shown on the permit; and
 The sum of the permissible axle, tandem axle, or group axle weight, whichever is less;
 Or except as described in OAR 734-082-0010 (2), ORS 818.030 (10).*

For weights beyond 15 axles and 150 feet of wheelbase, apply the following formula:

*1,600 times (the wheelbase in feet plus 40)
 when wheelbase is more than 30 feet*

