

# Permit Weight Table 1

(REVISED 04-2020)

The following exemptions apply to the table of weights shown below:

**Exemption 1:** Two consecutive tandem axles may weigh up to 34,000 pounds each if:

Minimum Axle Spacing Required	Interstate Highways	Non-Interstate Highways
30 feet or more	Permit Required	No Permit Required
36 feet or more	No Permit Required	No Permit Required

**Exemption 2:** A group of four axles consisting of a set of tandem axles and two axles spaced nine feet or more apart may have a loaded weight of more than 65,500 pounds and up to 70,000 pounds if:

Minimum Axle Spacing Required	Interstate Highways	Non-Interstate Highways
35 feet or more	Permit Required	No Permit Required

*Minimum axle spacing is the distance between the first and last axle of any group shown above.*

**Exemption 3:** An additional 550 pounds above the weights shown below is allowed for fully functional idle reduction systems.

**Exemption 4:** An additional 2000 pounds above the weights shown below is allowed for a vehicle that uses natural gas as its fuel source, or is powered primarily by means of an electric battery.

Wheelbase In Feet ▼	Number of Axles						Wheelbase In Feet ▼	Number of Axles					
	2	3	4	5	6	7 Or More		2	3	4	5	6	7 Or More
<b>4</b>	34,000	34,000	34,000	34,000	34,000	34,000	<b>31</b>	40,000	59,000	62,500	67,500	72,500	78,000
<b>5</b>	34,000	34,000	34,000	34,000	34,000	34,000	<b>32</b>	40,000	60,000	63,500	68,000	73,000	78,500
<b>6</b>	34,000	34,000	34,000	34,000	34,000	34,000	<b>33</b>	40,000	60,000	64,000	68,500	74,000	79,000
<b>7</b>	34,000	34,000	34,000	34,000	34,000	34,000	<b>34</b>	40,000	60,000	64,500	69,000	74,500	80,000
<b>8 &amp; less</b>	34,000	34,000	34,000	34,000	34,000	34,000	<b>35</b>	40,000	60,000	65,500	70,000	75,000	80,000
<b>Over 8</b>	38,000	42,000	42,000	42,000	42,000	42,000	<b>36</b>	40,000	60,000	66,000	70,500	75,500	80,000
<b>9</b>	39,000	42,500	42,500	42,500	42,500	42,500	<b>37</b>	40,000	60,000	66,500	71,000	76,000	80,000
<b>10</b>	40,000	43,500	43,500	43,500	43,500	43,500	<b>38</b>	40,000	60,000	67,500	71,500	77,000	80,000
<b>11</b>	40,000	44,000	44,000	44,000	44,000	44,000	<b>39</b>	40,000	60,000	68,000	72,500	77,500	80,000
<b>12</b>	40,000	45,000	50,000	50,000	50,000	50,000	<b>40</b>	40,000	60,000	68,500	73,000	78,000	80,000
<b>13</b>	40,000	45,500	50,500	50,500	50,500	50,500	<b>41</b>	40,000	60,000	69,500	73,500	78,500	80,000
<b>14</b>	40,000	46,500	51,500	51,500	51,500	51,500	<b>42</b>	40,000	60,000	70,000	74,000	79,000	80,000
<b>15</b>	40,000	47,000	52,000	52,000	52,000	52,000	<b>43</b>	40,000	60,000	70,500	75,000	80,000	80,000
<b>16</b>	40,000	48,000	52,500	58,000	58,000	58,000	<b>44</b>	40,000	60,000	71,500	75,500	80,000	80,000
<b>17</b>	40,000	48,500	53,500	58,500	58,500	58,500	<b>45</b>	40,000	60,000	72,000	76,000	80,000	80,000
<b>18</b>	40,000	49,500	54,000	59,000	59,000	59,000	<b>46</b>	40,000	60,000	72,500	76,500	80,000	80,000
<b>19</b>	40,000	50,000	54,500	60,000	60,000	60,000	<b>47</b>	40,000	60,000	73,500	77,500	80,000	80,000
<b>20</b>	40,000	51,000	55,500	60,500	66,000	66,000	<b>48</b>	40,000	60,000	74,000	78,000	80,000	80,000
<b>21</b>	40,000	51,500	56,000	61,000	66,500	66,500	<b>49</b>	40,000	60,000	74,500	78,500	80,000	80,000
<b>22</b>	40,000	52,500	56,500	61,500	67,000	67,000	<b>50</b>	40,000	60,000	75,500	79,000	80,000	80,000
<b>23</b>	40,000	53,000	57,500	62,500	68,000	68,000	<b>51</b>	40,000	60,000	76,000	80,000	80,000	80,000
<b>24</b>	40,000	54,000	58,000	63,000	68,500	74,000	<b>52</b>	40,000	60,000	76,500	80,000	80,000	80,000
<b>25</b>	40,000	54,500	58,500	63,500	69,000	74,500	<b>53</b>	40,000	60,000	77,500	80,000	80,000	80,000
<b>26</b>	40,000	55,500	59,500	64,000	69,500	75,000	<b>54</b>	40,000	60,000	78,000	80,000	80,000	80,000
<b>27</b>	40,000	56,000	60,000	65,000	70,000	75,500	<b>55</b>	40,000	60,000	78,500	80,000	80,000	80,000
<b>28</b>	40,000	57,000	60,500	65,500	71,000	76,500	<b>56</b>	40,000	60,000	79,500	80,000	80,000	80,000
<b>29</b>	40,000	57,500	61,500	66,000	71,500	77,000	<b>57 or</b>	40,000	60,000	80,000	80,000	80,000	80,000
<b>30</b>	40,000	58,500	62,000	66,500	72,000	77,500	<b>more</b>						

The loaded weight of any group of axles, vehicle, or combination of vehicles shall not exceed that specified in the table of weights shown above or any of the following:

- The manufacturer's side wall tire rating but not to exceed 600 pounds per inch of tire width.
- 600 pounds per inch of tire width.
- 20,000 pounds on any one axle, including any one axle of a group of axles.
- 34,000 pounds on any tandem axle.
- The sum of the permissible axle, tandem axle, or group of axle weights shown above, whichever is less.

Note exemptions 1 - 4 above.