

ISSUED TO

EMERGENCY RELIEF RESPONDERS
 EMERGENCY RELIEF
 STATEWIDE, SC, 0000000000
 USDOT #:

VEHICLE INFORMATION

Vehicle Type: **SEMI TRUCK/TRACTOR & TRAILER**
 Power Unit VIN: **XXXXXXXXXXXXXXXXXX**
 Power Unit Plate: **N/A (NA)**
 Trailer Plate: **N/A (NA)**
 Trailer Length: **53'**

Load Description: **ESSENTIAL GOODS AND PRODUCTS IN RESPONSE TO HURRICANE HELENE UNDER SC EXECUTIVE ORDER 2024-24** Load Length: **53'** Overhang

Overall Dimensions Front: **3'** Rear: **15'**

Width: **14'** Height: **13'6"** Length: **75'**

Official State Issued document

Gross Vehicle Weight (lbs): **90000** # Axles: **5**

Axle Group	Steer	Tandem	Tandem
Group Weight(lbs)	10000	40000	40000

Axles	1-2	2-3	3-4	4-5
Axle Spacing (ft-in)	10-0	5-0	20-0	5-0

PERMIT RESTRICTIONS

- When hauling a load in excess of 12' in width, a civilian escort required to travel in front of the load on two-lane highways.
- Escorts are required to display a minimum of one (1) flashing amber, strobe amber or rotating amber light, mounted on top of all escort vehicles. Lights shall be operational during movement with a minimum 500 feet visibility at 360 degrees. Vehicle lights cannot be used or substituted for warning lights. Headlights shall be on at all times while escorting.
- Escorts are required to display signs or banners on the front and on the rear of the escorting vehicle or above the roofline of the escorting vehicle, visible from the front and the rear. The sign or banner shall be at least 12 inches high x 7 feet wide. The sign or banner must read OVERSIZE LOAD or WIDE LOAD with black letters 10 inch high and 1.5" wide on yellow background. The sign shall be displayed as to be clearly legible and readable by oncoming traffic at all times and shall not conceal the license plate or lights.
- There shall be direct two-way radio communication between the escorting vehicle(s) and the towing vehicle at all times. An escorting vehicle(s) shall not escort or communicate with more than one towing vehicle at a time.
- A flashing or strobe amber light must be displayed on the rear of the load visible for 500 feet at 360 degrees.

- Signs or banners shall be displayed on both the front of the transporting vehicle and on the rear of the transporting vehicle or on the rear of the load. The sign shall be displayed as to be clearly visible and legible by oncoming traffic at all times. The sign or banner shall be at least 12 inches high x 7 feet wide. The sign or banner must read OVERSIZE LOAD or WIDE LOAD with black letters 10 inches high x 1.5" wide on yellow background. The sign/banner shall not conceal the license plate or lights.
- Fluorescent red or fluorescent orange colored flags, not less than 18 inches square, shall be displayed at each outer four corners of the load. Turn signals and brake lights must be displayed in working order.

GENERAL CONDITIONS

- No travel shall be allowed during inclement weather such as heavy rain or fog when visibility is restricted to less than 500 ft. Travel prohibited during periods of high wind or when highways are slippery or hazardous due to ice, snow, or sleet.
- Travel is prohibited over posted bridges with weight. Bridges may become posted along the permitted route during the permit date range. It is the responsibility of the permittee to contact the permit office for route modification.
- Detour vertical obstructions as necessary. The mover shall be responsible for checking all overhead vertical clearances and shall make provisions for raising or removal of overhead wires, cables, traffic signals, etc. at least three (3) days in advance of move.
- Permittee must exercise caution and use flagmen where necessary over narrow roadways and bridges.
- Reduce speed when traveling through SCDOT work zone construction sites. Permittee is responsible for immediately replacing to SCDOT standards all traffic devices (signs, cones, barrels, etc.) that are knocked over or destroyed upon contact.
- Pursuant to SC Code of Law 57-3-130 (B)(3)(c), it is the responsibility of the carrier to comply with all Federal Motor Carrier Safety Regulations and applicable State and Federal Laws, including, but not limited to, speed, tire size, brakes, and lighting.
- The towing vehicle must be a minimum 3/4 ton truck or truck tractor and must be in compliance with all recommendations by the manufacturer for the load being hauled and the trailer being utilized, this includes all recommended equipment on the towing vehicle and the trailer. The hauler must be in compliance with all applicable state and federal laws relative to commercial carriers.
- At all railroad grade crossings the carrier shall comply with 56-5-2725 of the SC Code of Law.
- Loads shall be transported by a vehicle, or combination of vehicles, so that the least width or length dimension becomes the width of the load. The load shall be transported such that no part of it will extend across the centerline of the road, except when necessary to avoid a collision with objects located near the edge of the roadway.

ROUTE INFORMATION

Origin: **FROM STATE LINE AND POINTS WITHIN SOUTH CAROLINA OVER US & SC HIGHWAYS ONLY.**
****NO LOAD WITH WEIGHT SHALL TRAVERSE A POSTED BRIDGE****

Destination: **FROM STATE LINE AND POINTS WITHIN SOUTH CAROLINA OVER US & SC HIGHWAYS ONLY.**
****NO LOAD WITH WEIGHT SHALL TRAVERSE A POSTED BRIDGE****

Total Mileage: **300**

Route: **WITH THIS SPECIAL PERMIT, LOADS EXCEEDING 8 FEET, 6 INCHES (8'6") IN WIDTH SHALL BE ALLOWED TO TRAVEL ON ALL NON-INTERSTATE ROUTES WITHIN THE NATIONAL NETWORK.**

Route Return:

ORIGINAL PERMIT SHALL BE SIGNED AND CARRIED IN TOWING VEHICLE DURING MOVEMENT

I certify that I am familiar with all SC traffic, motor vehicle, and other laws and requirements governing this move and will be in full compliance during movement. I agree that all dimensions and weights shown above are correct. I agree to move at my own risk and assume limited liability caused by this movement for any and all reasons including routing error, act, or omission by the State of South Carolina, and its departments or employees. I understand that this permit shall be open to inspection at any time by any uniformed officer or authorized agent of the authority granting the permit.

Permittee Signature

Date